SAFETY DATA SHEET

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:

POLYBAC #1183 - PART B

Company:

POLYGEM INC.

PO Box 609

West Chicago, Illinois 60185

Telephone:

630-231-5600

630-231-5604 (Fax Line)

Emergency Telephone Number:

1-800-535-5053

USA

01-352-323-3444

International

Section 2 - HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to the Regulation (EC) No. 1272/2008

Acute Dermal Toxicity Category 4
Acute Oral Toxicity Category 4

Skin Sensitization Category 1

Skin Corrosion/Irritation Category 1B

Chronic Aquatic Toxicity Category 2

Classification according to the Regulation Directive 199/45/EC: [Xn] Harmful, [C] Corrosive, [N] Dangerous to the Environment

information Concerning particular hazards for human and environment:

Product Description: This product is grey heavy paste with a sweet amine odor

Health Hazards: Corrosive, Severe eye irritant; Respiratory Irritant, may cause skin sensitization.

Flamability Hazards: This product is flammable above it's fashpoint of 380° (195 C)

tivity Hazards: None known.

onmental Hazards: The environmental effects of this product have not been investigated; however it is not expected to cause

significant adverse effects.

Emergency Considerations: Emergency responders must wear proper personal protective equipment (and have appropriate fire suppression

equipment) suitable for the situation to which they are responding.

Classification system:

This classification is according to the latest editions of the EU-lists, and extended by company and literature data.

2,2 Label elements

Labeling according to Regulation (EC) no. 1272/2008:

Hazard Pictograms:



\<u>'</u>



S07



GHS09

Signal Word: Danger

Hazard-determining component of labelling: Diethylenetriamine

Hazard Statements:

H302: Harmful is swallowed

H313: May be harmful in contact with skin H317: May cause an allergic skin reaction H335: May cause respiratory irritation

Precautionary Statements

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash hands thoroughly after handling

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area

P273: Avoid release to the environment.

P^^0: Wear protective gloves/protective clothing/eye protection.

onse Statements

P337+P313If eye irritation persists:Get medical advice/attention.

P370+P378-In case of fire:Use appropriate mediafor extinction

Page 1 of 4

www.polygem.com

P302+P353: IF ON SKIN: Wash with plenty of soap and waterfor extinction

P391: Collect spillage

P403+P235: Store in well ventilated place. Keep cool.

P501: Dispose of content and/or container in accordance with local, regional,national, and/or international regulations.

Hazard Description

HMIS-ratings (scale 0 - 4)

CHEMICAL NAME				
HEALTH	3			
FLAMMABILITY	1			
中国文字中的文本的 可以完全	0			
PERSONAL PROTECTION	F			

2.3 Other Hazards

None Known

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200). Unlisted ingredients are not "hazardous" per the OSHA standard.

Section 3: Hazards Identifications					
Chemical Name	CAS#	OSHA PEL ⁻	ACGIH TLV	WT%	
Benzyl Alcohol	100-51-6	N/E	N/E	5-20%	
Nonyi Phenol	25154-52-3	N/E	N/E	5-20%	
Vestamin IPD	2855-13-2	N/E	N/E	5-20%	
TOFA reaction products with TEPA	68953-36-6	N/E	N/E	5-20%	
Tetraethylenepentamine	112-57-2	N/E	N/E	<5%	
Silica, amorphous, fumed, crystalline free	112945-52-5	N/E	N/E	2	

*ALL INGREDIENTS ARE REGISTERED ON TSCA.

*Unless otherwise noted, all PEL and TLV Values are reported as 8 hour time weighted averages (TWA)

*T/S - Trade Secret

Emergency Overview:

Mild or moderate eye irritation.

May cause skin irritation.

Harmful if swallowed.

HMIS RATING:

HEALTH-3, FLAMMABILITY-1, REACTIVITY-0

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective

equipment recommendations.

Potential Health Effects

Eye contact:

Mild or moderate irritation, possible minor temporary comea injury.

Skin contact:

May cause skin irritation on prolonged or repeated exposure.

Skin absorption:

Not considered toxic.

Inhalation:

May cause nasal irritation, central nervous system depression or lung injury.

Chronic effects of over exposure:

NONE

Section 4: First Aid Measures

EMERGENCY & FIRST AID PROCEDURES:

Eyes:

Flush with plenty of water and get medical attention. Keep eye lids apart. Wash within 1 minute

of contact for maximum results.

Skin:

Promptly wipe clean with paper or cloths and wash with soap and water. Remove contaminated

clothing before reuse. Attention should be paid to hair, nose and eyes.

Inhalation: Ingestion:

In case of exposure to high concentration of vapor or mist, remove person to fresh air.

if large amounts are swallowed, induce vomitting. Seek medical attention. May cause burns to

mouth and throat.

Primary routes of entry:

Inhalation, Ingestion, skin and eye contact.

Carcinogenity:

This product does not contain 0.1% or more of any substance which is listed as a carcinogen

by NTP, IARC or OSHA.

Page 2 of 4

www.polygem.com

Section 5: Fire Fighting Measures

Flash Point: Test Method: 234 F

Setaflash Closed Cup

Lower Flammability Limit: Upper Flammable Limit:

N/A N/A

Water, Foam, Carbon Dioxide, Dry Chemicals or Fog.

Recommended Extinguishing Media:

sial Fire Fighting Procedures:

Firefighters should wear protective goggles and self contained breathing apparatus to avoid

inhalation of smoke or vapors. Remove all ignition sources.

Unusual Fire or Explosion Hazards

(conditions to avoid):

May produce hazardous furnes or hazardous decomposition products, such as carbon dioxide, carbon monoxide, hydrogen sulfide, oxides of sulfur and nilrogen.

Section 6: Accidental Release Measures

Special Protection:

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred.

Steps to be taken in case of material is released or spilled:

Ventilate the area. Absorb splll with suitable absorbent material and place into a closed container. Prevent material from entering waterways. Wear protective equipment during cleanup. Use eye and skin protection.

Transport Emergency Phone Number:

(INFOTRAC) 1-800-535-5053

Section 7: Handling and Storage

Handling:

Harmful or Imitation material. Avoid contact and avoid breathing the material

Use only in a well ventilated area.

Storage:

Store in a cool, dry place.

Ventilation:

standards (29 CFR 1910134). Not required for properly ventilation area.

Local exhaust and general ventifation is recommended.

J Protection:

Nitrile Rubbers gloves.

Eye Protection:

Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exits for eye contact with splashing or spraying liquid,

or airborne material; Have an eye wash station available.

Skin and Body Protection:

Avoid skin contact by wearing chemically resistant gloves and long sleeved

shirt. An apron may be appropriate if splashing can occur.

Section 9: Physical and Chemical Properties

Physical state:

Gel

Color:

Gray

Odor: Weight by gallon: Amine Odor

15 lbs

Solids (% by weight)

100

V.Q.C.

0 g/L

Bolling range:

335 F

Melting point:

N/E

Density: Percent volatile: 1.04

Vapor density (air=1):

N/D Not Volatile

Vapor pressure (mm Hg):

N/E

Evaporation rate:

N/A < 0.1%

Water miscibility:

www.polygem.com Page 3 of 4

Section 10: Stability and Reactivity

Stability:

Stable

Incompatibility:

Strong oxiders, epoxy resin, and amine mixtures especially when hot.

Hazardous polymerization:

Will not occur.

Hazardous decomposition products:

Oxides of Carbon and Phenolics under burning conditions

Conditions to avoid:

Heat and warm storage

Section 11: Toxicological Information

Chemical Name

LD50/LC50

Modified Allphatic Polyamine

Not established

Overview:

Section 12: Ecological Information

No ecological information available.

Section 13 Disposal Considerations

To the best of our knowledge, this product does not meet the definition of hazardous waste under U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via Incineration at an approved facility is recommended. Consult state, local or provincial authorities for more restrictive requirements.

Section 14: Transport Information

Consult Bill of Lading for transportation information

DOT: CORROSIVE LIQUID N.O.S. IATA: CORROSIVE LIQUID N.O.S.

Section 15: Regulatory Information

OSHA Hazard Communication Standard (29 CFR 1910.1200) Hazard Class(es): N/A

SARA Hazard Classification:

SARA Title III Regulations (40 CFR 370):

N/A

SARA Section 313 Listed Ingredients:

This material does not contain any substance which is subject to the reporting

requirements of 40 CFR 372.

DOT Proper Shipping Name:

Corrosive Liquid N.O.S. (Modified Aliphatic Polyamine)

UN Number:

UN1760

Section 16: Other Information

This information is furnished without warranty, representation inducement or license of any kind, except that is accurate to the best of Polygem Inc. knowledge, or obtained from sources believed by Polygem Inc. to be accurate and Polygem Inc. does not assure any legal responsibility for use reliance upon the same. Customers are encouraged to conduct their own tests. Before using any product, please read its label.

Revision Date: 06/2015

Page 4 of 4

www.polygem.com